

■ PERFORMANCE AND SPECIFICATION

1. Performance

Heater	Heat Output	W	6000
	Air Flow Volume	m ³ /h	360
	Power Consumption	W	210
Air Conditioner	Cooling Capacity	W	6100
	Air Flow Volume	m ³ /h	530
	Power Consumption	W	260

2. Specification

Ventilation and Heater Core	Heater Core	Type		SFA (Straight Flow Aluminum)-II	
		Size		201.5 x 150 x 27	
		W x H x L	mm (in.)	(7.9 x 5.9 x 1.1)	
	Fin Pitch		mm (in.)	1.5 (0.06)	
	Blower	Motor Type		K70 BMM	
		Fan Type		Semi Sirocco	
Fan Size		165 x 70			
Dia. x H		mm (in.)	(6.5 x 2.8)		
Air Conditioner	Condenser	Type		MF (Multi-Flow)-IV	
		Size		720 x 370.2 x 16	
		W x H x L	mm (in.)	(28.3 x 14.6 x 0.6)	
	Fin Pitch		mm (in.)	3.15 (0.12)	
	Evaporator	Type		RS (Revolutionary super-slim Structure)	
		Size		266.3 x 251 x 38	
		W x H x L	mm (in.)	(10.5 x 9.9 x 1.5)	
	Fin Pitch		mm (in.)	2.6 (0.1)	
	Compressor	Type		7SBH17	
		Pulley		Steel with Magnetic Clutch	
Refrigerant	Type		HFC 134a		
	Charge Volume		g	450 to 550	